




# Hardener with adhesion promoter

RZ5200

| | |
|---|---|
| Formulation | Water-based |
| What it is used for | Coating |
| Where to use it | Outdoors, Indoors |
| On which object | Furniture, Frames and skirting boards, Fences and enclosures, Windows and shutters, Gazebos, garden houses and doghouses, Garden furniture, Watercrafts, Floorings and poolsides, Indoor floorings, Doors, Front doors and entry doors, Claddings, Claddings and boiserie, Outdoor beams, Indoor beams |
| Material | Wood |
| Final result | Visible wood grain |

## Fields of application

Furniture, doors and windows, exterior and interior claddings, balconies, fences, matchboardings, beams, exterior and interior floorings, platforms, jetties, docks and poolsides.

## Information

RZ5200 is a hardener specifically designed for water-based systems, formulated to significantly improve adhesion to the substrate and the chemical and physical resistance of the coating film.

## Instructions

In combination with RP1060 Grain Filler, RP1160 Transparent Semi-Glossy Topcoat, RP2260 Transparent Matt Topcoat and RP3360 Transparent Glossy Topcoat, add 10% of the hardener . For the products Natural Effect Topcoat RO 3000, Suite Skin RH 1005, Hybrid Resolve RS 80xx and Hi-Deck Hydro-Oil RK 10xx, the recommended addition is 5%.

## Packaging

50 ml



Copyright © 2026 Renner Italia S.p.A

## Quick info

| See instructions | Storage | Ready to use | Painting | Pot life |
|---|---|---|---|---|
| 5–10 % | 5 °C | | 15 °C | 4 hours |

## Available colours

RZ5200
**neutral**

This translation is provided for information purposes only. Product availability and compliance with local requirements must be verified for each country before purchase or use.



Copyright © 2026 Renner Italia S.p.A