

Uniform Plus

RS3010

Formulation	Water-based
What it is used for	Coating
Where to use it	Outdoors, Indoors
On which object	Furniture, Fences and enclosures, Frames and skirting boards, Windows and shutters, Gazebos, garden houses and doghouses, Garden furniture, Doors, Front doors and entry doors, Claddings, Claddings and boiserie, Outdoor beams, Indoor beams
Material	Ceramic, Laminated wood, Wood, Metal, Plastic, Wall, PVC, Glass, Wicker
Final result	Full colour

Safety information

Harmful to aquatic life with long lasting effects. **Contains**: 2-METHYL-4-ISOTHIAZOLIN-3-ONE, mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. If medical advice is needed, have product container or label at hand. Keep out of reach of children. This product contains microplastics. To minimize release into the environment: cover the work area before application, collect spills with absorbent material, do not pour the product into drains, and do not rinse the container before disposal. Collect any wash water and dispose of it at a waste collection center. Avoid release to the environment. Read label before use. The empty container must be delivered closed, with the original cap, to a recycling center. Check the dispositions of your municipality. EU limit value for this product (cat. A/e): 130 g/l. Maximum VOC content for this product 55 g/l.

Fields of application

Wood, metal, plastic, PVC, glass, ceramic, steel, galvanised steel sheet, plaster, plasterboard. For indoor and outdoor use.

Information

Uniform Plus is a white water-based multi-surface primer, made of acrylic resins, suitable for the application on materials, that are difficult to be coated, such as doors, windows, wood claddings and other materials. In case of application on wood, Uniform Plus is an anti-tannin product, therefore it stops the migration of wood extractives, i.e. tannins and oily substances. Uniform Plus effectively covers coffee, marker, pastel, rust and old coatings stains. The thixotropic features make the product particularly suitable for vertical application. RS3010 is ready to use if applied by brush or roller; must be diluted max. 10% with water by spray gun.

Instructions

Raw wood. Sand with 150-180 grit sandpaper, clean the surface from dust and grease and apply 2-3 coats of product. ***Coated wood.*** Sand with 180-240 grit sandpaper. If some coating films peeled off, make sure to remove them completely. Clean the surface from dust and grease, then apply Uniform Plus in 2-3 coats. ***Other surfaces.*** Before the application, clean the surface

Copyright © 2026 Renner Italia S.p.A

from dust and grease. To improve the application, it is possible to sand slightly the support with 180-240 grit sandpaper and apply 2 or 3 coats of product. To decorate rusty metal surfaces, remove the rust with sandpaper or metallic brush. Apply an antirust product, then apply Uniform Plus.

Overcoating

Decogrip Solution RE20xx, Prestige range RBxxx0, Floorings and Furniture Topcoat RPxx60.


Packaging

2.5 L, 500 ml

Quick info

Storage 5 °C	Final drying time 24 hours	Drying time between coats 4-24 hours	Mix it well before use	Specific weight 1.3 ± 0.1 g/cm³	8.5 ± 1.0
Ready to use	Yield 8–12 m²/L	Solid content 58 ± 3 %	Painting 10 °C	Viscosity 5000 ± 300 cP	Brush Spray gun Roller

Available colours



RS3010
White

Copyright © 2026 Renner Italia S.p.A