




Floor Prestige

RB2x70



Formulation	Water-based
What it is used for	Coating
Where it is used	Outdoors, Indoors
What it is used on	Furniture, Fences and enclosures, Frames and skirting boards, Windows and shutters, Gazebos, garden houses and doghouses, Garden furniture, Indoor floorings, Tiles, Doors, Front doors and entry doors, Claddings, Claddings and boiserie, Outdoor beams, Indoor beams
Material	Concrete, Ceramic, Cotto tiles, Granite, Stoneware, Laminated wood, Wood, Marble, Metal, Wall, Plastic, PVC, Glass, Wicker
Final effect	Full colour

Certifications



HACCP



Toy safety



Safety information

Contains: Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one (3:1); 1,2-Benzisothiazol-3(2H)-one. May produce an allergic reaction. If medical advice is needed, have product container or label at hand. Keep out of reach of children. This product contains microplastics. To minimize release into the environment: cover the work area before application, collect spills with absorbent material, do not pour the product into drains, and do not rinse the container before disposal. Collect any wash water and dispose of it at a waste collection center. The empty container must be delivered closed, with the original cap, to a recycling center. Check the dispositions of your municipality. EU limit value for this product (cat. A/e): 130 g/l. Maximum VOC content for this product 80 g/l.

Fields of application

Wood, metal, glass, plastic and wall. Both indoor and outdoor use. **Information:** Golden Prestige is a metallic topcoat for the contemporary luxury. No sanding and no stripping required. On nonporous surface (glass, plastic, etc.) it is recommended the application of RBxx90 as a primer to improve the adhesion in the closest colour to the chosen one of RB5x90.

Instructions

Before the application. Remove dust and grease by means of Clean & Grip VY0500. Do not use other degreasers or thinners available on the market: they could leave residuals on the surface and compromise the adhesion of Floor Prestige. *How to prepare a surface treated with wax.* Before applying Floor Prestige, remove the wax with a dewaxer; then rinse and degrease by means of Clean & Grip VY0500. *How to prepare a very smooth surface.* On particularly smooth surfaces, such as marble, slightly sand with 220 grit sandpaper for metal. It is fundamental removing completely the dust. Slightly sanding, specifically suitable for the treatment of smooth substrates, is useful for every surface since they promote the coating adhesion. *How to treat grout lines.* Grout lines between tiles are porous. Therefore, they accumulate dirt compromising the coating adhesion and the aesthetic result. Cleaning grout lines is very important and it could be done mechanically by means of steel brush or other tools. *How to treat surfaces under extreme stress.* Add 4% of Adhesion Promoter RY0406 to Floor Prestige range in case of surfaces under severe chemical and/or mechanical stress (bath tubs, gym floorings, laboratories floorings, clinics, hair salons, pet grooming services, etc.). Adhesion Promoter strengthens the bond with the surface to be coated and improves coating resistances.

Application. Spread the product over the surface. Before the application of the second coat, let it dry off at least 2-4 hours according to the environmental conditions. 2 or 3 coats are suggested for surfaces with high traffic. On surfaces highly subjected to wear, Floor Prestige can be protected with Floorings and Furniture Topcoat RP2260. **Drying.** Carefully ventilate the room to promote the correct drying of Floor Prestige. In order to get a state-of-the-art drying, avoid too much abundant application; excessive weight of product could impede a complete drying, leaving the coating wet and less performing.

Overcoating

Floorings and Furniture Topcoat RP2260.



Available colours



Rb2070

Dove grey



Rb2170

Papyrus



Rb2270

Concrete



Rb2370

Lead



Rb2470

Charcoal grey



Rb2570

Titanium